

# Randall®

A M P L I F I E R S

<b>RANDALL RG3003H</b>
<b>300 Watts @ 4 Ω</b>
<b>3 Channels with Gain and Level</b>
<b>Integrated Noise Gate with Threshold</b>
<b>EQ with Bass, Mid, Treble, Presence</b>
<b>Bass EQ Boost</b>
<b>Mid EQ Scoop</b>
<b>Switchable Serial effects loop</b>
<b>XLR Output with Ground Lift</b>
<b>RF1503 Footswitch switches all three Channels and Loop</b>

#### IMPORTANT SAFETY INSTRUCTIONS

1. Read these instructions.
2. Keep these instructions.
3. Read all warnings.
4. Follow all instructions.
5. Do not use this apparatus near water.
6. Clean only with a dry cloth.
7. Do not block any ventilation openings. Install in accordance with the manufacturer's instructions.
8. Do not install near any heat sources such as radiators, heat registers, stoves, or other apparatus (including amplifiers) that produce heat.
9. Use the correct safety purpose of the polarized or grounding type plug. A polarized plug has two blades with one wider than the other. A grounding type plug has two blades and a third grounding prong. The wide blade or the third prong are provided for your safety. If the provided plug does not fit into your outlet, consult an electrician for replacement of the obsolete outlet.
10. Protect the power cord from being walked on or pinched, particularly at plugs, convenience receptacles, and the point where they exit from the apparatus.
11. Only use attachments/accessories specified by the manufacturer.
12. Use only with a cart, stand, tripod, bracket, or other unit specified by the manufacturer, or used with the apparatus. When a cart is used, use caution when moving the cart/apparatus combination to avoid injury from tip-over.
13. Unplug this apparatus during lightning storms or when unused for long periods of time.
14. Refer all servicing to qualified service personnel. Servicing is required when the apparatus has been damaged in any way, such as power supply cord or plug is damaged, liquid has been spilled or objects have fallen into the apparatus, the apparatus has been exposed to rain or moisture, does not operate normally, or has been dropped.



#### Randall Warranty

Randall Amplifiers, a Division of U.S. Music Corporation warrants the product you have purchased to be free of defects in materials and workmanship in normal use for a period of two (2) years from the date of original purchase. This warranty shall run to the original purchaser when purchased from an Authorized Randall Dealer. The manufacturer warrants speakers for a period of (1) years. The manufacturer warrants tubes for a period of (90) days. Defective parts found during the applicable warranty period with proof of purchase will be replaced or repaired without charge if the complete product is returned to US Music Corp or any Authorized Randall Service Center within the U.S.A. Randall reserves the right to use materials readily available at the time of the repair. All Warranty service requires Proof of Purchase (sales receipt) to be presented at time of service request. Any repair or service performed by any person of entity other than an Authorized Service Center is not covered by this limited warranty. The customer pays transportation to and from Randall factory service or any Randall Authorized Service Center. Rental stock is warranted for (1) year from date of invoice to the Authorized dealer. Warranty on rental units is not transferable.

What is covered against manufacturing defects

Parts and Labor to correct any defect in materials used and any defect attributable to workmanship.

What is not covered:

Shipping Damage. Report damage upon receipt of item to the carrier (i.e. UPS). Freight carrier must be notified upon receipt of items to insure freight damage claim resolution. Shipping damage not filed with carriers within (48) hrs upon receipt will not be covered under warranty. Report any shipping damage within (48) hrs of receipt to the Randall Customer Service Dept at 1-800-877-6863, ext. 5120. Keep all original documents and packing materials to insure freight damage claim resolution. Merchandise that has been modified after original shipment from the Randall factory. Products whose serial numbers have been altered or removed. Exterior normal wear and tear damage to the finish due to misuse, operation outside the specified ratings, neglect or accident. Warranty claims by anyone other than the original purchaser. Randall is not responsible for any items left in protective covers or cases. (We strongly advise that all personal items such as chords, cables, tuners, etc... be removed!) freight charges to and from the factory or an Authorized service center on customer owned goods, any and all charges incurred from priority service requests (Rush Service) or priority shipping for replacement parts. Any and all charges if no problem is found.

#### Return Authorization

All items being returned for any reason must have a Return Authorization number. This RA# must be placed on the outside of the carton of the item being returned or the carton will be refused upon delivery. Please call the customer service department at 1-800-877-6863, ext. 5120, for the return authorization number. Dealer stock items will be returned to the dealer freight prepaid.

An Authorized Warranty Service Center must perform any and all field warranty service work. Customer will not pay for parts and/or labor provided the problem found is within warranty guidelines. Proof of purchase must be provided at the time of service request. Transportation charges to and from the Authorized Warranty Service Center are the responsibility of the customer. Rush service charges and special freight charges for required parts are not covered under warranty and are also the responsibility of the customer. If a unit is not easily transported to an authorized service center, the customer is responsible for technician travel charges. Any charges for labor or processing when no problem is found are also not covered under warranty. Any charges incurred for work performed by an unauthorized service center are the responsibility of the customer.

Warranty terms may vary per country, check warranty terms with local Distributor or at point of purchase.

# Randall®

A M P L I F I E R S


## RG3003H



# OPERATION MANUAL

For detailed product videos please visit our website at [www.randallamplification.com](http://www.randallamplification.com)

Congratulations on the purchase of your new **RANDALL** Amplifier! We at Randall Amplification appreciate that you chose the RG3003H Amplifier and wish you years of great tone and enjoyable playing time. Please review the safety instructions below and be aware that the documentation provided in this manual references 120volt USA versions of the models covered. Note that the POWER listed on the back of the unit should be for your countries' power standard.



1. 1/4" Guitar Input.
2. Channel selector switch toggles between 3 channels (footswitchable).
3. Channel 1 gain controls amount of pre amp drive to channel 1.
4. Bright switch adds Hi-Frequency EQ "Sparkle" to Channel 1.
5. Channel 1 volume controls the amount of Channel 1 signal being sent to the master volume output.
6. Channel 2 gain controls amount of pre amp overdrive to channel 2 - this will control the amount of "distortion".
7. Channel 2 volume controls the amount of Channel 2 signal being sent to the master volume output.
8. Channel 3 gain controls amount of preamp overdrive to channel 3 - this will control the amount of "searing distortion".
9. Channel 3 volume controls the amount of Channel 3 signal being sent to the master volume output.
10. The Bass knob controls the amount of low frequency equalization for the entire signal.
11. The BASS BOOST will enhance low EQ - Warning: use of boost with the Bass knob turned up can cause speaker damage.
12. The Middle knob controls the mid-frequency equalization for the entire signal.
13. The MID SCOOP will decrease middle EQ similar to a "smiley face" setting on a graphic EQ.
14. The Treble knob will control the amount of High frequency equalization for the entire signal.
15. The Presence knob controls the uppermost High EQ frequencies above the Treble EQ shelf.
16. NOISE GATE BYPASS removes the noise suppression circuit from the signal path.
17. THRESHOLD controls the Noise Reduction function. After setting your preferred gain and tone settings, play your guitar very softly and turn up the threshold until it begins to eliminate the softest notes then turn it slightly under that "threshold".
18. The MASTER VOLUME controls the amps volume going to whatever speaker cabinet is connected.
19. The PHONES output allows for headphones to be plugged in - *Note: speaker out is muted during headphone operation.*
20. STEREO MEDIA INPUT allows for 1/8" media source such as MP3 player to be inserted into signal to play along.
21. The POWER switch turns the amplifier on and off.
22. AC Inlet this jack is for the power cable supplied for your regions power - plug this cable in and the other side to the source.
23. SPEAKER OUTPUT #1 is parallel with Speaker output #2 and utilizes standard 1/4" with MINIMUM 4 OHMS LOAD FOR BOTH OUTPUTS #1 & #2 -*(this means maximum 2-8ohm cabs combined for both speaker outputs).*
24. SPEAKER OUTPUT #2 is parallel with Speaker output #1 and utilizes standard 1/4" with MINIMUM 4 OHMS LOAD FOR BOTH OUTPUTS #1 & #2 -*(this means maximum 2-8ohm cabs combined for both speaker outputs).*
25. XLR Line Out provides "mic cable" output to carry amp output signal to PA, mixing console or recording device.
26. GND LIFT - lifts the ground or "Earth" of the XLR OUT to avoid noise/hum when interfacing external gear via XLR.
27. EFFECTS LOOP RETURN - plug 1/4" guitar cable from the output from Effects pedal or device here.
28. EFFECTS LOOP SEND - plug 1/4" guitar cable to the input of Effects pedal or device here.
29. FOOTSWITCH - 7 PIN DIN connector of included 4 button RF1503 footswitch inserts here to operate.