



RB100 Bass Amplifier Operation Manual

1	_		USA
	EAR RRA	 ITED	

Randall guitar, bass speaker enclosures and amplifiers are warranted to be free from defects in materials and workmanship in normal use for a period of five (5) years from the date of original purchase. Electronics and electronic components are covered for three (3) years and speakers for two (2) years.

During that period, Randall will, at its option, repair or replace materials at no charge. Products must be delivered to Randall, freight prepaid or to an authorized Randall Service Center with the original sales receipt or other proof of purchase. Warranty excludes exterior finish, normal wear and tear, failure due to abuse or operation outside the specified ratings. Warranty applies to original purchaser only. Warranty gives you specific rights which vary from state to state. For more information regarding warranty or service please contact:

Randall Customer Service 444 East Courtland St. Mundelein, IL 60060 USA 847-949-0444

RETAIN FOR YOUR RECORDS

(Complete, detach and return to Randall within 10 days of purchase)				
NAME:	AGE:			
ADDRESS:				
CITY:	STATE: ZIP:			
EMAIL: Do you wish to receive Randall	s' E-newsletter? Yes No			
SERIAL NO.:				
DATE OF PURCHASE:/ //	RECEIPT NO.:			
DEALER NAME:				
CITY:	STATE: ZIP:			
WHERE DID YOU HEAR OF THIS RANDALL PRODUCT ?:				
Dealer Different Difference Catalog Difference Advertisement In:				
WHAT INFLUENCED YOU TO BUY THIS RANDALL PRODUCT?: (Check all applicable) Price Sound Appearance Dealer's Presentation Catalog and Specifications				
WHAT OTHER COMPONENTS WILL BE USED WITH THIS RANDALL PRODUCT?:				

Features of the RB100

- 15" high-performance Eminence driver with piezo tweeter
- 1/4" input jacks
- Pre-gain level: adjusts input volume level
- Contour: voicing adjustment for preamp
- Built-in compressor/limiter
- Bass, middle, treble controls with mid-frequency sweep
- 9-band graphic equalizer
- Balanced XLR line out
- Effects loop
- Headphone out
- Effects loop
- External speaker

Power Output: 100-Watts RMS @ 8ohms.

Effects Loop: Send 200mV Return 50k ohms

Signal Output: 0 db @ 600ohms

Dimensions: 21.5" W X 16.5" D X 29.5" X 29.5"H

IMPORTANT SAFEGUARDS

THESE WARNINGS APPLY TO ALL RANDALL ELECTRONIC PRODUCTS. PLEASE READ AND OBSERVE ALL WARNINGS AND INSTRUCTIONS CONTAINED IN THIS PAMPHLET, OWNER'S MANUAL AND THOSE ON YOUR RANDALL PRODUCT PRIOR TO ITS USE. RETAIN THESE WARNINGS FOR YOUR SAFETY AND REFERENCE.

WARNINGS AND SYMBOLS:



LIGHTNING FLASH: The lightning flash with an arrowhead within an equalateral triangle, is intended to alert the user of the presence of uninsulated DANGEROUS VOLTAGE within the product's enclosure that may be of significant magnitude to constitute risk of electric shock to persons.



EXCLAMATION POINT: The exclamation point within an equalateral triangle, is intended to alert the user of the presence of IMPORTANT OPERATING AND MAINTENANCE OR SERVICE INSTRUCTIONS in the Iterature

WARNING GRAPHIC ON PRODUCT:

accompanying the product.





PRECAUTIONARY WARNING:

RAIN AND MOISTURE: To reduce the risk of fire or electric shock, DO NOT EXPOSE THIS UNIT TO RAIN OR MOISTURE. Operators of electronic products should in no way be in contact with water.

GROUNDING: To prevent electric shock, DO NOT DEFEAT THE 3 PRONG GROUNDING PLUG on product's power cord. Do not use an adapter, extension cord or outlet unless the blades can be fully inserted to prevent blade exposure.

WARNING GRAPHIC ON PRODUCT:

CAUTION: TO PREVENT FIRE OR ELECTRICAL SHOCK, DO NOT EXPOSE TO RAIN OR MOISTURE

