



RH100 Owner's Manual 100 Watt Guitar Amplifier

5 YEAR LIMITED WARRANTY

Randall guitar, bass speaker enclosures and amplifiers are warranted to be free from defects in materials and workmanship in normal use for a period of five (5) years from the date of original purchase. Electronics and electronic components are covered for three (3) years and speakers for two (2) years.


During that period, Randall will, at its option, repair or replace materials at no charge. Products must be delivered to Randall, freight prepaid or to an authorized Randall Service Center with the

original sales receipt or other proof of purchase. Warranty excludes exterior finish, normal wear and tear, failure due to abuse or operation outside the specified ratings. Warranty applies to original purchaser only. Warranty gives you specific rights which vary from state to state. For more information regarding warranty or service please contact:

Randall Customer Service 444 East Courtland St. Mundelein, IL 60060 USA 847-949-0444

RETAIN FOR YOUR RECORDS

(Complete, detach and return to Rai	ndall within 10 days of purchase)		
NAME:		AGE:	
ADDRESS:			
CITY:		STATE:	ZIP:
EMAIL:	Do you wish to receive Randalls	' E-newsletter?	Yes No
SERIAL NO.:		MODEL NO.:	
DATE OF PURCHASE:	/ /	RECEIPT NO.: _	
DEALER NAME:			
CITY:		STATE:	_ ZIP:
WHERE DID YOU HEAR OF THIS	RANDALL PRODUCT ?:		
Dealer Deriend Catalog D	Advertisement In:		
WHAT INFLUENCED YOU TO BUY THIS RANDALL PRODUCT?: (Check all applicable) □ Price □ Sound □ Appearance □ Dealer's Presentation □ Catalog and Specifications			
WHAT OTHER COMPONENTS WILL BE USED WITH THIS RANDALL PRODUCT?:			



Additional Features: This amp offers several additional features including line out with independant level control, external speaker jack, effects loop with level controls, headphone jack, and footswitchable channels for gain 1/gain 2, and clean channel.

Power Output: 100W . THD0.2% (at 1 KHz 8Ω)

Power Consumption: 200VA

Input Sensitivity: -46dB

Controls (All Controls Set At 5): Bass: +/- 15db @ 50Hz Mid: +/- 10db @ 600Hz Treble: +/- 18db @ 3Hz Contour: +18db @ 15Hz

Effects Loop: Send 200mV Return 50k ohms

Signal Output: 0 db @ 600ohms

Dimensions: 885W x 335H x 345D

IMPORTANT SAFEGUARDS

THESE WARNINGS APPLY TO ALL RANDALL ELECTRONIC PRODUCTS. PLEASE READ AND OBSERVE ALL WARNINGS AND INSTRUCTIONS CONTAINED IN THIS PAMPHLET, OWNER'S MANUAL AND THOSE ON YOUR RANDALL PRODUCT PRIOR TO ITS USE. RETAIN THESE WARNINGS FOR YOUR SAFETY AND REFERENCE.

WARNINGS AND SYMBOLS:



LIGHTNING FLASH: The lightning flash with an arrowhead within an equalateral triangle, is intended to alert the user of the presence of uninsulated DANGEROUS VOLTAGE within the product's enclosure that may be of significant magnitude to constitute risk of electric shock to persons.



EXCLAMATION POINT: The exclamation point within an equalateral triangle, is intended to alert the user of the presence of IMPORTANT OPERATING AND MAINTENANCE OR SERVICE INSTRUCTIONS in the literature accompanying the product

WARNING GRAPHIC ON PRODUCT:



PRECAUTIONARY WARNING:



GROUNDING: To prevent electric shock, DO NOT DEFEAT THE 3 PRONG GROUNDING PLUG on products power cord. Do not use an adapter, extension cord or outlet unless the blades can be fully inserted to prevent blade exposure.

WARNING GRAPHIC ON PRODUCT:

CAUTION: TO PREVENT FIRE OR ELECTRICAL SHOCK, DO NOT EXPOSE TO RAIN OR MOISTURE

